



KÖSTER Color-Chips

Decorative colored chips for broadcasting into e.g. KÖSTER LF-VL, KÖSTER Universal Floor

Features

UV and chemically resistant decorative colored chips for broadcasting into the surface of KÖSTER LF-VL, KÖSTER Universal Floor, KÖSTER UC 100, etc.

Technical Data

Size approx. 2 mm
Standard color ("MF22") mixed: light grey
Other colors available upon request.

Fields of Application

For adding surface structure and decoratively enhancing the surface of KÖSTER LF-VL, KÖSTER Universal Floor, KÖSTER UC 100, etc. KÖSTER Color Chips are suitable for indoor and outdoor use.

Substrate

For all water based and solvent free resin coatings, especially KÖSTER LF-VL, KÖSTER Universal Floor and KÖSTER UC 100.

Application

For surface design of e.g. KÖSTER LF-VL:

KÖSTER Color Chips are broadcast by hand into the still fresh surface so that a uniform distribution is achieved. The KÖSTER Color Chips are to be thrown upwards and not directly into the fresh surface. Prepared surfaces should always be completed treated in one work step to ensure a homogenous appearance.

For use with KÖSTER Universal Floor:

For contrast floor decoration approx 300 g / m² of KÖSTER Color-Chips are evenly applied with a compressed air-powered cup gun. When broadcasting over the entire surface, approx. 0.7 - 1.0 kg / m² of KÖSTER Color-Chips are applied evenly in excess, also with a cup gun. After the coating has hardened, excess material can be picked up with an industrial vacuum cleaner and reused for further coating works. When applying the sealing coat made of KÖSTER CT 127 1C Silane Primer, we recommend wearing spiked shoes.

Consumption

Minimum 50 g / m² as a decorative, non-covering surface decoration. Approx. 300 g / m² when broadcasting to rejection.

Packaging

CT 429 005	5 kg carton
CT 429 005 Z07	5 kg carton
CT 429 005 Z17	5 kg carton
CT 429 005 Z19	5 kg carton
CT 429 010	10 kg carton

Storage

Store in a cool and dry area. Carefully reseal opened cartons. If stored in originally sealed packages the KÖSTER Color Chips can be stored for a minimum of 2 years.

Related products

KÖSTER CT 127 1C Silane Primer
KÖSTER LF-BM
KÖSTER Construction Resin
KÖSTER CT 215 Universal Floor
KÖSTER UC 100
KÖSTER LF-VL
KÖSTER TS transparent

Prod. code CT 127 005
Prod. code CT 160
Prod. code CT 165 025
Prod. code CT 215
Prod. code CT 251 026
Prod. code CT 271
Prod. code CT 320

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.